

Chargers



Type	Compact Charger	Standard Charger	Fast Charger*
Charging current	max. 2 A	max. 4 A	max. 6 A
Voltage	100–240 V	220–240 V	220–240 V
Size (L × W × D)	approx. 160 × 75 × 45 mm	approx. 190 × 86 × 54 mm	approx. 200 × 90 × 60 mm
Cable lengths	Power cable: approx. 1.5 m; battery cable: approx. 1.0 m		
Plug	country-specific power plug		
Weight	approx. 600 g	approx. 800 g	approx. 1000 g
Operating temperature	-0 to +40°C	-0 to +40°C	-0 to +40°C
Storage temperature	+10 to +40°C	+10 to +40°C	+10 to +40°C
Compatibility	Active Line/Active Line Plus/Cargo Line/Performance Line/ Performance Line CX/Classic + Line compatible using adapter plug		
Charging time			
PowerPack 300	50% in approx. 2 h, 100% in approx. 5 h	50% in approx. 1 h, 100% in approx. 2.5 h	50% in approx. 1 h, 100% in approx. 2.5 h
PowerPack 400 / PowerTube 400	50% in approx. 2.5 h, 100% in approx. 6.5 h	50% in approx. 1.5 h, 100% in approx. 3.5 h	50% in approx. 1 h, 100% in approx. 2.5 h
PowerPack 500 / PowerTube 500	50% in approx. 3.5 h, 100% in approx. 7.5 h	50% in approx. 2 h, 100% in approx. 4.5 h	50% in approx. 1.2 h, 100% in approx. 3 h
PowerTube 625	50% in approx. 4.2 h, 100% in approx. 8.8 h	50% in approx. 2.1 h, 100% in approx. 4.9 h	50% in approx. 1.4 h, 100% in approx. 3.7 h
DualBattery 1250	50% in approx. 8.4 h, 100% in approx. 17.6 h	50% in approx. 4.2 h, 100% in approx. 9.8 h	50% in approx. 2.8 h, 100% in approx. 7.4 h

* Charging current is limited to 4 A for the PowerPack 300 and Classic + Line batteries.